

# G-LENZ<sup>®</sup> SECURITY

H.265  
IP CAMERA

## GEIP 39731

IP CAMERA BULLET- 3MP  
NIGHT COLOR  
PoE - AUDIO



**Feature:**

**Video Compression**

H.264 / H.265 video compression, achieving ultra-low bit-rate, superb high-definition picture quality.

**IR-CUT**

Support IR-CUT,with ICR and automatic color change to achieve day/night function.

**Digital Wide Dynamic**

Support 2D/3D noise reduction digital wide dynamic.

**Plug & Play**

Plug and Play, support cloud technology easy to achieve network penetration and alarm information pushed.

**Easy to Operate**

Support OSD menu-do what you want and design your need. Support NVR/HVR, Support Onvif

### EXPERIENCE Series

<b>H.265</b> MPEG-4/AVC	<b>HD</b> <b>3MP</b>	Full Color Night Vision	IR
<b>AGC</b> Auto Gain Control	<b>WDR</b> Wide Dynamic Range	ICR	<b>COLOR</b> NTSC / PAL
<b>PoE</b>	IP66 Water Proof	Vandal Proof	Audio

FREE APPS DOWNLOAD: XMEYE



24/7 FULL-TIME  
COLOR NIGHT VISION



# GEIP 39731

IP Camera  
Bullet 3MP  
Night Color  
PoE - Audio



**G-LENZ**®  
**SECURITY**

TECHNICAL SPECIFICATIONS			
Model	GEIP 39731 IP CAMERA OUTDOOR 3MP NIGHT COLOR		
Camera	Image Sensor	High Resolution 3MP	
	Resolution	3MP	
	Effective Pixel	2304(H)X1296(V)	
	Compression	H.264 /H.265 /JPEG/AVI/MPEG	
	TV System	PAL/ NTSC	
	Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25 1/10000Sec	
	S/N Ratio	≥ 52dB	
	Scanning System	Progressive	
	Video Output	Network	
	Features	Day/Night	Color/ B&W (IR-CUT)
Image Config		Saturation / Brightness / Contrast / Sharpness, Mirror, 3D NR, White Balance	
Defog Mode		Support	
BLC, WDR		Support	
Motion Detection		Support	
Privacy Masking		3 Rectangular Zone	
Recording Mode		NVR / NAS / CMS / Web	
Audio		Support	
Lens		Focus Length	Board Lens 3.6mm
		Focus Control	Fixed
	Lens Type	Fixed	
Night Vision	Infrared LED	4 Pcs Warm LED	
	Night Color	Support Full Color Night Vision	
	Infrared Distance	30 M	
	IR Status	Support Smart IR	
	IR Power On	Smart IR Auto Control	
Network	Ethernet	RJ-45 (10/100Base-T)	
	Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS, RTP, RTSP, RTCP,NTP,SMTP	
	ONVIF	Support ONVIF 2.4	
	PoE	Support IEEE 802.3af	
	P2P	YES, Support QR Code	
	Video Delay	0.35 (Within the Lan)	
	Main Stream 1	1920x1080@30fps, 1280x720@30fps	
	Sub Stream	720x480@15fps, 720x480@30fps	
	Tri Stream	352x288@15fps, 352x288@30fps	
	IE Browser	IE8-11, Google Chrome, Firefox, Safari, Mac Safari	
Smart Phone	iPhone, iPad, Android, Android Pad		
General	Housing	IP66, Metal Case	
	IR Cut Filter	YES	
	Operation Temperature	20°C ~ +60°C RH95% Max	
	Storage Temperature	20°C ~ +60°C RH95% Max	
	Power Source	DC 12V ± 10%,850MA	
	Dimension	157(W) x 70(H) x 66(D) mm	
	Weight	650g	