

# G-LENZ<sup>®</sup> SECURITY

## H.265 / A.I SMART PTZ CAMERA

A.I  
Human  
Tracking

1080P

Pan Rotation  
355°

Tilt Rotation  
110°



## GWIP-2100

TRUE HUMAN TRACKING  
WITH A.I HUMAN DETECTION  
FULL HD 1080P - 2MP  
WIFI CONNECTION

Feature:

### Video Compression

H.264 / H.265 video compression, achieving ultra-low bit-rate, superb high-definition picture quality.

### AI Human Tracking

Supporting AI automatic human shape detection and tracking, with high sensitivity but no dead angle and no misdeclaration, and also supporting smart human shape playback

### Night Vision

Support night vision starlight sensor.

### Mobile Surveillance

Mobile App access are available, via which the monitoring, devices management and other functions can be easily handled.


### Easy to Operate

Support OSD menu-do what you want and design you need. Motion detection alarm sound can be set as your favorite voice.

## MINI PTZ SECURITY CAMERA



FREE APPS DOWNLOAD: P6SLITE





# GWIP-2100

Smart PTZ Camera  
 A.I Human Tracking  
 Two-Way Audio  
 Support Cloud NVR



**G-LENZ**®  
**SECURITY**

TECHNICAL SPECIFICATIONS		
Model	GWIP-2100 PTZ A.I WiFi Camera	
System	Main processor	T31N
	Operating system	Embedded LINUX operating system
Video	Image sensor	1/2.9 CMOS Sensor
	Video coding standard	H.265/H.264
	Effective resolution	1920*1080/1280*720
	Effective Pixels	2.0 M pixels
	Video frame rate	1-20fps(default setting 20)
	Video stream	256kbps-12288kbps(Default variable bit rate, support custom) (APP)
	S/N ratio	S/N ratio≥69dB
	Backlight compensation (BLC)	AUTO
	Automatic white balance (AWB)	AUTO
	Video output	Easy VMS Client/Mobile APP/Video APP(UVC/UVA)
	Motion Detection	Stand by
	Capture function	Stand by
	Audio	Coding standard
Audio input		Built-in on-board microphone MIC
Audio output		External 8Ω/MAX 1.5W Speaker
Video management	Video mode	Mobile video, alarm video, timed video, human video
	Video saving	TF card/cloud storage
	Alarm trigger	Human alarm, motion detection alarm, speaker alarm, video alarm, capture, send email
Internet	Network protocol	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Search (Support P6S IP camera, DVR, NVS and etc.)
Other	TF card capacity	Maximum 128GB (common FAT32 format)
	Working voltage	Standard DC-12V (wide voltage 10-16V)
	Working current	320mA ±20mA
	Working environment	-20°C — 70°C
Size and Weight	Size	Diameter 80mm, height 105mm
	Net weight (bare camera)	627G
	Weight	727G