

G-LENZ[®] SECURITY

H.265 / A.I

SMART CAMERA BATTERY,
INTELLIGENT DUAL LIGHT

GWIP-2300

RECHARGEABLE BATTERY CAMERA
DIRECT CONNECTION 4G SIMCARD
A.I HUMANOID DETECTION
GUARD POSITION FUNCTION

Feature:

Video Compression

H.264 / H.265 video compression, achieving ultra-low bit-rate, superb high-definition picture quality.

Rechargeable Battery Powered

Build-in rechargeable battery. Support solar panels above 5V 15W. Battery 4000 mAh

AI Smart Function

Supporting AI automatic human shape detection with high sensitivity. Support vehicle detection, pet capture and package

IR Night Color Vision

Infrared light(night vision distance of 7 meters), day and night 24-hour monitoring, IR-CUT switching, daytime color, night vision more clear

4G Simcard Wireless Connection

Easy and simple using direct 4G Simcard, support telkomsel & south east asia bands.



SMART CAMERA PTZ OUTDOOR

H.265 MPEG-4/AVC	HD 4MP	Connect Via 4G 4G SIMCARD	 Full Color Night Vision
 Motion Detection	 MOBILE SURVEILLANCE	 Up to 256GB	IP65 Weather Proof
 2 Way Audio	 Rechargeable Battery	 Humanoid Detection	

FREE APP DOWNLOAD: P6SLITE




24/7 FULL-TIME
COLOR NIGHT VISION

Night
Color



GWIP-2300 4G

Smart PTZ Camera Outdoor
 Rechargeable Battery
 Wireless 4G Connection
 IP65 Weather Proof
 Two-Way Audio



G-LENZ®
SECURITY

TECHNICAL SPECIFICATIONS		
Model	GWIP-2300 Smart Camera Battery Outdoor 4G Connection 4MP (2K)	
System	SOC	Embedded LINUX operating system
Image Sensor	Sensor	1/2.9" CMOS sensor
	Lens	f: 4.0mm, F1.6, 3MP
	Viewing angle	Diagonal 98° Horizontal 83° Vertical 44°
	Minimum illumination	Day mode 1Lux, night vision mode 0.01Lux
Audio	Audio input	Sensitivity - 42dB
	Audio output	External 4Ω / 2W speaker
	Two-way intercom	Full duplex
Video	Video compression method	H.265
	Video stream	135kbps-2048kbps
	Image frame rate	15 fps
	Maximum image size	2560*1440 (4MP)
	Night vision light source	IR CUT filter automatic switching
	Day and night mode	Intelligent dual-light/full-color white light/normal night vision
4G	LTE-FDD	B1/B3/B5/B8
	LTE-TDD	B34/B38/B39/B40/B41
	Network protocol	HTTP,TCP/IP,IPV4,UPNP,RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP,IP Search(Support P6S IP camera, DVR, NVS and etc.)
Video	Video mode	Alarm trigger, timed recording
	Video storage	Local Micro SD card (up to 256G)
	Function	Intelligent
	Audible alarm	When equipped with dual light boards, it supports sound and light alarm
	Alarm notification	Mobile APP message push
Solar panels and batteries	Solar panels	5V 15W solar panel
	Battery	Four 21700 4000mA batteries
	Charging board	Built-in single-chip microcomputer system, which can intelligently manage the power supply of equipment
	Power saving function	Support power monitoring and power saving function
PTZ	PTZ rotation angle	H (horizontal) 0° ~ 350° stepless rotation; V (vertical) 60° ~ -20°
	Preset position	Support 6 preset position settings
Power supply	Operating Voltage	Standard DC-5V, 1.5A
Environment	Working environment	-10° ~ 45°C /10% ~ 80% (no condensation)
	Storage environment	-20°C ~ 60° /0% ~ 90% (no condensation)